

CATERPILLAR HOSE 3/8" XT-3 1650016 NEW

Product Images



Description

Description:Caterpillar XT-3 ES (Enhanced Spiral) hose exceeds the requirements of SAE 100R12 for the best in reliable hose and coupling performance. Cat XT-3 ES hose provides up to 20 times more abrasion resistance than the industry’s best rubber-covered hose, due to an exclusive cover formulated and manufactured by Caterpillar. Cat XT-3 ES hose works at half of the SAE bend radius without sacrificing cold flex capability.Attributes:• Hose ID: 9.5 mm (0.375 in)• Hose dash size: -6• Hose OD: 20.5 mm (0.81 in)• Min Burst Pressure: 110,317 kPa (16,000 psi)• Max Working Pressure: 27,580 kPa (4,000 psi)• Min Bend Radius: 64 mm (2.52 in)• Temperature Range: -40° C to +121° C (-40° F to +250° F)• Bulk unit of measure: Inch• Fabric reinforced, synthetic rubber tube; four plies of spirally-wrapped high tensile steel wire reinforcement, separated by layers of synthetic rubber. Oil, weather, and abrasion resistant synthetic rubber outer cover• For use with collet-type reusable, skive type or crimp-on permanent, skive type couplingsApplication:Very high pressure service with petroleum base hydraulic fluids. MSHA approved cover. Consult your owner's manual or contact your local Cat Dealer for more information.

Additional Information

| | | |
|----------------------------------|-----------------------|-------------------|
| Brand | CATERPILLAR | |
| Condition | ORIGINAL | |
| Applications suitable (detailed) | Name | Models |
| | MOTOR GRADER | 120 |
| | WHEEL-TYPE LOADER | 966F 966F II 992C |
| | ENGINE - INDUSTRIAL | G3516 |
| | WHEEL TRACTOR-SCRAPER | 621G |