

CATERPILLAR HOSE 3/8" XT-3 1650016 NEW

Product Images



Описание

Description: Caterpillar XT-3 ES (Enhanced Spiral) hose exceeds the requirements of SAE 100R12 for the best in reliable hose and coupling performance. Cat XT-3 ES hose provides up to 20 times more abrasion resistance than the industry's best rubber-covered hose, due to an exclusive cover formulated and manufactured by Caterpillar. Cat XT-3 ES hose works at half of the SAE bend radius without sacrificing cold flex capability. Attributes: • Hose ID: 9.5 mm (0.375 in) • Hose dash size: -6 • Hose OD: 20.5 mm (0.81 in) • Min Burst Pressure: 110,317 kPa (16,000 psi) • Max Working Pressure: 27,580 kPa (4,000 psi) • Min Bend Radius: 64 mm (2.52 in) • Temperature Range: -40° C to +121° C (-40° F to +250° F) • Bulk unit of measure: Inch • Fabric reinforced, synthetic rubber tube; four plies of spirally-wrapped high tensile steel wire reinforcement, separated by layers of synthetic rubber. Oil, weather, and abrasion resistant synthetic rubber outer cover • For use with collet-type reusable, skive type or crimp-on permanent, skive type couplings Application: Very high pressure service with petroleum base hydraulic fluids. MSHA approved cover. Consult your owner's manual or contact your local Cat Dealer for more information.

Additional Information

Бренд	CATERPILLAR	
Состояние	ОРИГИНАЛ	
Подходящие приложения (подробно)	Name	Models
	MOTOR GRADER	120
	WHEEL-TYPE LOADER	966F 966F II 992C
	ENGINE - INDUSTRIAL	G3516
	WHEEL TRACTOR-SCRAPER	621G